

PRODUCT DATASHEET - LARGE REMOTE CONTROL TERMINAL



INTELLI-SENSE

Addressable Device

TI-002323-ST

DESCRIPTION

The remote terminals (active repeater panel) utilise the same graphical LCD user interface that can be found on the Intelli-Sense series fire panels and are based upon the same advanced, flash based, microprocessor technology.

The Intelli-Sense panels and remote terminals can communicate over the same 2-core network cable.

They feature an integral network interface incorporating a special screen termination to prevent mains frequency earth-loop currents flowing between network nodes.

The Intelli-Sense-NeT network operates as a true peer-to-peer system with full cross panel reporting, control and cause-and-effect functionality of up to 2000 zones.

All remote terminals incorporate buzzer mute, view, enable/disable and test facilities with dedicated system and navigation keys for simple user control.

The display information is fully programmable by individual zone or sector and can display any combination of fires, faults, pre-alarms or plant alarms. E.g. can display all information in its own sector, but can only show fire signals from other sectors of a building.

KEY FEATURES

- The RCT has additional sector based control keys for Silence, Mute, Resound and Reset, which allows other networked panels to selectively respond to controls as programmed. E.g. on a site with multiple buildings, a user may be allowed to silence and reset fires originating in their own building. Fires originating from other buildings are displayed but cannot be reset.
- Fully on-site programmable via onboard alphanumeric keypad or PC configuration tools.
- View all information from across the network
- By using flash memory and an advanced graphical display the remote terminals can be easily configured to operate in virtually any language, with any character set and allows for the installer's logo and company details to be displayed on the LCD display during normal operation.
- Fully programmable push buttons for remote isolation, class change or general alarms. compatible with a wide range of routing equipment.
- Networked for System Display or Control
- Programmable switch input
- Graphical LCD display
- Intelli-Sense-NeT compatible
- Slide-in Labels
- Small, robust and compact
- 24V DC operating voltage
- 1-year warranty
- Disable/enable options

TECHNICAL SPECIFICATION

| | |
|--------------------|--|
| Display | White backlit 240x64 graphical LCD |
| LED Indicators | 2 red (1 x Fire, 1 x Alarm), 1 green (Power) & 18 amber (Fault & System) |
| Keypads | Alpha numeric keypad, navigation keys & on-board buzzer mute facility |
| Controls | System keys for Mute, reset, Silence, Resound & Evacuation |
| Key-Switch Input | Optional level 2 access enable key switch |
| Power Supply Input | 24 VDC, 115mA (/FT: 150mA) operating range 15-30V |

Call: **1800 120 3473 / +91 9540 666 666**
+91 120 4223473

Visit our website: ceasefire.in

Email: response@ceasefire.in

Ceasefire Industries Pvt. Ltd.

Plot No. 4, Second Floor, Sector-135,
Noida - Greater Noida Expressway,
Noida - 201 301, Uttar Pradesh [India]

PRODUCT DATASHEET - LARGE REMOTE CONTROL TERMINAL



INTELLI-SENSE

Addressable Device

TECHNICAL SPECIFICATION (CONT.)

| | |
|----------------------------|---|
| External Supply Monitoring | Monitored external fault input |
| Number of Fire Zones | 2000 |
| USB/Serial Ports | 1 x USB & 1 x RS232 |
| Programming | Via on-board keypad or PC running Windows tools |
| Enclosure | Steel IP30 |
| Cable Entry | 20mm knock-outs.4 x top and 4 x rear |
| Colour | RAL7035 |
| Size H x W x D mm | Enclosure: 263 x 300 x 42. Back box only (when recessing) 263 x 300 x30 |
| Metal work Options | Semi flushing bezel, special finishes including stainless & chrome |

Other Codes and Options

| | |
|--------------|---|
| TI-002323-ST | Remote Control Terminal (RCT) c/w Programmable Push Buttons and LEDs - Standard Version |
| TI-002323-FT | Remote Control Terminal (RCT) c/w Programmable Push Buttons and LEDs - Fault Tolerant Version |



Call: **1800 120 3473 / +91 9540 666 666**
+91 120 4223473

Visit our website: ceasefire.in

Email: response@ceasefire.in

Ceasefire Industries Pvt. Ltd.
Plot No. 4, Second Floor, Sector-135,
Noida - Greater Noida Expressway,
Noida - 201 301, Uttar Pradesh [India]